



SPALY51G

Design by Ryosuke Fukusada

Collection consisting of aluminium suspended lamps.
Available in several colours and sizes.

Typology: SUSPENSION LAMP

Ratings

- Built in line voltage **LED** module
- CCT 3000 K
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off dimmable trailing edge
- Die cast aluminium body, painted
- Opalescent diffuser

Product code composition




ALYSOID


Type	Article	Colours	Catene / chains	Source
SP	ALY 51 G	AN anthracite grey wrinkled	NI black polished nickel	LED 20W - diffused beam 3000K available on request 2700K
			OT natural brass	

IP20 CRI90 220-240VAc **LED** ~1800 lm 90 lm/W
 example composition code | SP | ALY51G | AN | NI | LED

Available colors



OT
Anthracite grey and natural brass



NI
Anthracite grey and black polished nickel

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER _____ NOTES _____
 SPALY51GAN_ _LED _____

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources.
 Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.